

LAY-FLAT TIP

Features

The Lay-Flat hose allows for improved flow control and lower placement rates than standard concrete boom tip hoses. Ideal for ICF forms, columns and tall walls where space is at a minimum. Con Forms meets or exceeds strict safety regulations such as the North American ASME B30.27 2009.

Benefits

- Meets/exceeds ASME requirements
- 1/3 the weight
- Operator Friendly
- More consistent flow at lower placement rates
- Ease of pour in tight areas
- Bright color for visibility and safety
- Superior resistance to weather and aging
- Cleans up easily



Working Pressure
85 bar
1233 psi

Lay-Flat Boom Tip Hose

Length	End Style	Dry Weight	F.W.C. Weight	Part Number
10'	Hevi-Duty	24 lbs.	180 lbs.	H40LF10D1A
12'	Hevi-Duty	26 lbs.	214 lbs.	H40LF12D1A
15'	Hevi-Duty	30 lbs.	264 lbs.	H40LF15D1A
20'	Hevi-Duty	36 lbs.	348 lbs.	H40LF20D1A
25'	Hevi-Duty	41 lbs.	432 lbs.	H40LF25D1A
10'	148mm	36 lbs.	209 lbs.	H40LF10RM1A
15'	148mm	42 lbs.	293 lbs.	H40LF15RM1A
20'	148mm	48 lbs.	377 lbs.	H40LF20RM1A

Custom lengths are available upon request. Consult Factory

800-223-3676



CONFORMS.COM

